

specialized working gloves

safety, design & comfort


BASIC 27

ref. SP-11

BASIC 35

ref. SP-13

BASIC 40

ref. SP-14

peso MEDIO


DESCRIPCION

PVC sobre soporte algodón interlock.

EMPLEOS ACONSEJADOS

Industria metálica. Mantenimiento. Galvanoplastia. Petroquímica.



Talla / Size Taille / Tamanho

BASIC 27 / 35
8 - 9
BASIC 40
8 - 9 - 10
EN-388


4 1 2 1



Soporte de algodón interlock

 Cotton interlock liner
Support cotton interlock
Supporte algodão interlock

EN-374-3

AKL

Table / Table / Tableau / Tabela

EN-374-2


Pasa / Pass / Passen / Passa



CAT. II



basic 27

basic 35

basic 40



basic 27 270mm

basic 35 350mm

basic 40 400mm


FEATURES

SOLVENT (27-35-40) PVC on a cotton interlock liner. Rough no slipping. SOLVENT PLUS 40. PVC on a cotton jersey liner. Rough surface. BASIC 27/35/40. PVC on a cotton interlock liner.

RECOMMENDED USE

SOLVENT (27-35-40)/SOLVENT PLUS 40/ BASIC 27/35/40. Metal treatments. Maintenance. Plating. Petro-chemical.

TRAITS

SOLVENT (27-35-40) PVC sur coton interlock. Rugueux traitement antiglissant. SOLVENT PLUS 40. PVC sur coton jersey. Rugueux traitement antiglissant. BASIC 27/35/40. PVC sur coton interlock.

UTILISATION RECOMMANDÉE

SOLVENT (27-35-40)/SOLVENT PLUS 40/ BASIC 27/35/40. Industrie métallique. Entretien. Galvanoplastie. Pétrochimie.

CARACTERÍSTICAS

SOLVENT (27-35-40). PVC sobre algodão interlock. Rugoso anti deslizando. SOLVENT PLUS 40. PVC sobre algodão jersey. Rugoso anti deslizando. BASIC 27/35/40. PVC sobre algodão interlock.

USO RECOMENDADO

SOLVENT (27-35-40)/SOLVENT PLUS 40/ BASIC 27/35/40. Indústria metálica. Manutenção. Galvanoplastia. Petroquímica.