




## 7809TORX



## PUNTAS TORX®

- Vaso con punta TORX® con cuadrado 1/2"
- No es adecuado para uso con máquinas de impacto
- Aleación de acero de alto rendimiento
- Pulido fino
- Estriado
- ISO 1174
- DIN 3120
- SB = Embalaje en blister con información de producto

|                | 731415  |   |     | I<br>mm | L<br>mm | D<br>mm |      | g  |
|----------------|---------|---|-----|---------|---------|---------|------|----|
| 7809TORX-T20   | 1811730 | 5 | T20 | 23      | 60      | 22      | M 4  | 50 |
| 7809TORX-T25   | 1811747 | 5 | T25 | 23      | 60      | 22      | M 5  | 50 |
| 7809TORX-T27   | 1811754 | 5 | T27 | 23      | 60      | 22      | –    | 55 |
| 7809TORX-T30   | 1811761 | 5 | T30 | 23      | 60      | 22      | M 6  | 55 |
| 7809TORX-T40   | 1811778 | 5 | T40 | 23      | 60      | 22      | M 8  | 60 |
| 7809TORX-T45   | 1811785 | 5 | T45 | 23      | 60      | 22      | –    | 60 |
| 7809TORX-T50   | 1811792 | 5 | T50 | 23      | 60      | 22      | M 10 | 65 |
| 7809TORX-T55   | 1811808 | 5 | T55 | 23      | 60      | 22      | M 12 | 80 |
| 7809TORX-T60   | 1811815 | 5 | T60 | 23      | 60      | 22      | M 14 | 85 |
| SB7809TORX-T20 | 3004017 | 1 | T20 | 23      | 60      | 22      | M 4  | 50 |
| SB7809TORX-T25 | 3004024 | 1 | T25 | 23      | 60      | 22      | M 5  | 50 |
| SB7809TORX-T27 | 3004031 | 1 | T27 | 23      | 60      | 22      | –    | 55 |
| SB7809TORX-T30 | 3004048 | 1 | T30 | 23      | 60      | 22      | M 6  | 55 |
| SB7809TORX-T40 | 3004055 | 1 | T40 | 23      | 60      | 22      | M 8  | 60 |
| SB7809TORX-T45 | 3004062 | 1 | T45 | 23      | 60      | 22      | –    | 60 |
| SB7809TORX-T50 | 3004079 | 1 | T50 | 23      | 60      | 22      | M 10 | 65 |
| SB7809TORX-T55 | 3004086 | 1 | T55 | 23      | 60      | 22      | M 12 | 80 |
| SB7809TORX-T60 | 3004093 | 1 | T60 | 23      | 60      | 22      | M 14 | 85 |